

# Product data sheet

## TSA 355

Automatic or manual revolving door system for three- or four-leaf doors



### Product features

Individual choice of diameter, passage height and surfaces
Extensive additional equipment
Robust and proven drive technology up to a diameter of 4000 mm
Easy installation of the door system without lifting tools
Fast commissioning thanks to pre-cabled and configured sensors
Certification in accordance with EN 16005

### Application Areas

Three- and four-leaf door systems
Interior and exterior doors with high access frequency
Representative building entrances with large incidence of light
Façades with narrow post-rail constructions
Diameters from 1800 up to 4000 mm possible

### Product Data Table

Manual operation	Yes
With speed limiter (optional)	Yes
Fully automatic operation	Yes
Break-out function (BO)	Yes
Inner diameter (min.)	1700 mm
Inner diameter (max.)	3900 mm
For 3-leaf door systems	Yes
For 4-leaf door systems	Yes
Clear passage height*	3000 mm
Canopy height (min.)	300 mm
Side elements version	8 mm LSG
Version of roof structure	optical sheet metal covering, waterproof roof with waterspout
Illumination	with roof variant, according to customer wishes
Floor covering	Entrance mat, Floor mat according to customer wishes
Hot-air curtain system	hot water air curtain, Electric air curtain, integrated in the suspended ceiling
Night-time closer layout	Outside
Night-time closer type	Manual
Night-time closer design	8 mm LSG
Lock	Manual
Approvals	EN 16005