

Product data sheet

Slimdrive SLT



Automatic telescopic sliding door system for use in narrow
glass façades



AREAS OF APPLICATION

- Double and four leaf sliding door systems
- In confined spaces with small clear opening width or little space next to the door opening
- Interior and exterior doors with high access frequency
- Opening widths of 1000 to 3600 mm possible
- Door leaf weights of up to 80 kg per leaf
- Suitable profile systems are fine-framed profile systems with ISO glass and integrated all-glass systems (IGG)

PRODUCT FEATURES

- Two parallel-running tracks guide the door leaves and thus achieve high opening widths
- Very quiet running, low-wear direct current drive with a height of only 7 cm
- Can be networked via CAN bus and integrated into building technology management systems
- Independent error recognition and recording
- Freely configurable inputs and outputs for different functions
- Integrated battery for emergency opening and closing in the event of a power failure
- Various mechanical and electrical locks are optionally available

TECHNICAL DATA

Productname	Slimdrive SLT
For 2-leaf door systems	Yes
For 4-leaf door systems	Yes
ISO glass fine-framed	Yes
Integrated all-glass system (IGG)	Yes
Depth	247 mm
Leaf weight (max.) 2-leaf	80 kg
Leaf weight (max.) 4-leaf	70 kg
Opening width 2-leaf	1000 mm - 3000 mm
Opening width 4-leaf	1600 mm - 3600 mm
Operating temperature	-15 °C - 50 °C
IP rating	IP20
Disconnection from mains	Main switch in the drive
Approvals	DIN 18650, EN 16005, DIN EN ISO 13849: Performance Level D

ACCESSORY

GC 363

Combined detector for activating and protecting automatic sliding doors with ten different infrared light curtain configuration settings



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
GC 363 SF Combined detector	Combined detector for the activation and safeguarding of automatic sliding doors	151240	acc. to RAL	270 x 58 x 58 mm	24 V
GC 363 SF Combined detector	Combined detector for the activation and safeguarding of automatic sliding doors	151239	black	270 x 58 x 58 mm	24 V
GC 363 R combined detector	Combined detector for the activation and safeguarding of automatic sliding doors	151237	black	270 x 58 x 58 mm	24 V
GC 363 R combined detector	Combined detector for the activation and safeguarding of automatic sliding doors	151238	acc. to RAL	270 x 58 x 58 mm	24 V

ELBOW SWITCH

Stainless steel elbow switch with IP65 IP rating for activating automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
Elbow switch EFT	Very flat design / IP rating IP65	119898	Stainless steel	75 x 250 x 17 mm	Surface-mounted installation

ELBOW SWITCH

Plastic elbow switch, IP rating IP30, for activation of automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
GEZE plastic elbow switch	Very flat design, IP rating IP30	114077	stainless steel optic	90 x 180 x 23 mm	Surface-mounted installation
GEZE plastic elbow switch	Very flat design, IP rating IP30	114078	white	90 x 180 x 23 mm	Surface-mounted installation

Slimdrive SLT



LS990 ELBOW SWITCH

Elbow switch for activating automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
LS 990 elbow switch	IP rating IP30 H=223mm	128583	Stainless steel	81 x 223 x 18 mm	Flush-mounted installation
LS 990 elbow switch	IP rating IP30 H=223mm	128582	Stainless steel	81 x 223 x 51 mm	Surface-mounted installation
LS 990 elbow switch	IP rating IP30 H=223mm	141041	alpine white	81 x 223 x 51 mm	Surface-mounted installation
LS 990 elbow switch	IP rating IP30 H=223mm	141042	alpine white	81 x 223 x 18 mm	Flush-mounted installation

LED SENSOR FOOT SWITCH

Switch for activating automatic doors



Name	Description	Ident-No.	Type of installation
LED sensor foot switch	Capacitive push button for activating automatic door systems. Protection rating IP69K	182936	Floor

LED SENSOR SWITCH

Switch for activating automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Length
LED sensor switch	Capacitive push button with blue LED lighting and haptic Braille lettering for activating automatic door systems. Protection rating IP69K	137529	black	100 x 100 x 10 mm	100 mm
LED sensor switch glass	Capacitive push button with blue LED lighting for activating automatic door systems. Protection rating IP69K	143412	white	100 x 100 x 8 mm	100 mm

ROCKER PUSH BUTTON

Activation of automatic swing, sliding, folding, revolving and curved sliding doors



Name	Ident-No.	Colour	Dimensions	Type of installation
GEZE rocker push button	094033	alpine white		Flush-mounted installation
GEZE rocker push button LS 990	098396	Stainless steel		Flush-mounted installation
GEZE rocker push button E2	094013	white RAL 9016		Flush-mounted installation
GEZE rocker push button	094174	white		Flush-mounted installation
GEZE rocker push button AS 500	120888	alpine white	80 x 80 x 9 mm	Flush-mounted installation
GEZE rocker push button	098395	alpine white		Flush-mounted installation

PULL SWITCH

For triggering calls in barrier-free bathrooms or WCs



Name	Description	Ident-No.	Dimensions	Type of installation
Pull switch	incl. pull chain 500 mm long	008607	36 x 94 x 34 mm	Surface-mounted installation

GC 365

Combined detector for activating and protecting automatic sliding doors with four different infrared light curtain configuration settings



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
Combined detector GC 365 R	Combined detector for the activation and safeguarding of automatic sliding doors	160283	black	267 x 61 x 38 mm	24 V DC
Combined detector GC 365 SF	Combined detector for the activation and safeguarding of automatic sliding doors	160284	black	267 x 61 x 38 mm	24 V DC

Slimdrive SLT



DPS

Display programme switch for setting the mode of operation for automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
Display programme switch DPS with OFF key	Configuring the mode of operation as well as service case and parameter setting for automatic doors / with 5x control keys, 2x7 segment display, alphanumeric fault display, IP rating IP40	151524	alpine white	80 x 80 x 53 mm	24 V DC
Display programme switch DPS without OFF switch	Configuring the mode of operation as well as service case and parameter setting for automatic doors / with 4x control keys, 2x7 segment display, alphanumeric fault display, IP rating IP40	155809	alpine white	80 x 81 x 5.3 mm	24 V DC
Display programme switch DPS with OFF key and key switch SCT	in combined double frame without Euro profile half cylinder	155810	alpine white	80 x 151 x 50 mm	24 V DC

GC 302

Radar movement detector for activating automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Output
GC 302 R radar movement detector	Radar movement detector for activating automatic doors	124087	black	176 x 62 x 52 mm	Potential-free relay contact
GC 302 SV radar movement detector	Activation of automatic doors in the escape direction	124090	acc. to RAL	176 x 62 x 52 mm	Voltage output
GC 302 R radar movement detector	Radar movement detector for activating automatic doors	124088	acc. to RAL	176 x 62 x 52 mm	Potential-free relay contact
GC 302 SV radar movement detector	Activation of automatic doors in the escape direction	124089	black	176 x 62 x 52 mm	Voltage output

Slimdrive SLT



GC 304

Radarmovement detector with individual adjustment option for activating automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Output
GC 304 R Radar movement detector	Activation of all GEZE automatic doors	130651	black	120 x 80 x 50 mm	Electrical relay

GC 306

Non-contact proximity switch for activating automatic doors



Name	Description	Ident-No.	Colour	Operating voltage	Length
GC 306 (with hand pictogram)	Proximity switch to activate automatic doors	163028	alpine white	24 V DC	84 mm
GC 306 (with GEZE pictogram)	Proximity switch to activate automatic doors	163029	alpine white	24 V DC	84 mm

GC 339

Self-monitoring light curtain for the protection of automatic swing, revolving and curved sliding doors as well as windows



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
GC 339	Self-monitored light curtain for protecting automatic doors, suitable for GEZE GC 363	151252	acc. to RAL	209 x 58 x 47 mm	24 V
GC 339	Self-monitored light curtain for protecting automatic doors, suitable for GEZE GC 363	151251	black	209 x 58 x 47 mm	24 V

Slimdrive SLT



GC 341

Self-monitored light curtain for the protection and activation of automatic sliding doors, suitable for GC 365



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
GC 341	Self-monitored light curtain for the protection and activation of automatic sliding doors, suitable for GC 365	160285	black	267 x 61 x 38 mm	24 V DC

MINI LED SENSOR SWITCH

Activation of all GEZE automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
LED sensor switch 20 mm	Capacitive push button for activating automatic door systems. Protection rating IP69K	143273	aluminium, matt	28.5 x 28.5 x 6.5 x 14.5 mm	24 V DC

MPS

Mechanical programme switch for setting the mode of operation for automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
Mechanical programme switch MPS-D	Setting of the mode of operation of automatic doors with rotary button, IP rating IP40 / suitable for switch ranges with 55x55mm switch insert	118417	alpine white	80 x 80 x 24 mm	24 V DC
Mechanical programme switch MPS	Setting of the mode of operation of automatic doors with rotary button, LED fault display, IP rating IP40 / suitable for switch ranges with 55x55mm switch insert	113226	alpine white	80 x 80 x 24 mm	24 V DC
Mechanical programme switch MPS-D-ST	Setting of the mode of operation of automatic doors with key, LED fault display, IP rating IP40, incl. 2x identically locking keys / suitable for switch ranges with 55x55mm switch insert	118418	alpine white	80 x 80 x 24 mm	24 V DC
mechanical programme switch MPS ST	Setting of the mode of operation of automatic doors with key, LED fault display, IP rating IP40, incl. 2x identically locking keys / suitable for switch ranges with 55x55mm switch insert	113227	alpine white	80 x 80 x 24 mm	24 V DC

Slimdrive SLT



AS 500

AS emergency stop switch with glass pane and five interchangeable labels ("Nottaster öffnen", "Notschalter", "Emergency switch", "Tür schließen" and without text)



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
Emergency stop switch AS 500	Rocker control switch with glow lamp, glass pane and five interchangeable labels ("Nottaster öffnen", "Notschalter", "Emergency switch", "Tür schließen" and an empty label)	120881	alpine white/red	80 x 80 x 21 mm	Flush-mounted installation

SCT STAINLESS STEEL

Key switch stainless steel for authorised activation and for changing the mode of operation of automatic doors



Name	Description	Ident-No.	Colour	Type of installation
Key switch spring return without euro profile half cylinder	Mounting with claws or screws, spring return on one side (key can be removed in the central position), cover can only be removed with key, aluminium leaf, IP rating IP54	098870	silver-coloured	Flush-mounted installation
Key switch with euro profile half cylinder and three keys	Adjustable stay-put or spring return on both sides (key can be pulled out in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	137056	silver-coloured	Surface-mounted installation
Key switch stay-put without euro profile half cylinder	Attachment with claws or screws, stay-put on both sides (key can be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54 / Attachment with claws or screws, stay-put on both sides (key can be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	111357	silver-coloured	Flush-mounted installation

SCT KEY SWITCH

Key switch for authorised activation and for changing the mode of operation of automatic doors



Slimdrive SLT



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
SCT key switch	2-pin with Euro profile half cylinder, spring return on both sides, without AS 500 frame	118478	alpine white		
SCT key switch	Single-pin without euro profile half cylinder, spring return on one side	117996	alpine white	80 x 80 x 11 mm	Flush-mounted installation

SCT 221

Key switch for authorised activation and changing the mode of operation of automatic doors, surface and flush-mounted



Name	Description	Ident-No.	Colour	Dimensions	Type of installation
Key switch SCT 221	One-sided switching operation, with Euro profile half cylinder and three keys / Spring return on one side (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054533	silver-coloured	75 x 75 x 50 mm	Surface-mounted installation
Key switch SCT 221	One-sided spring return, without euro profile half cylinder / Spring return on one side (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054240	silver-coloured	75 x 75 x 11 mm	Flush-mounted installation
Key switch SCT 221	One-sided switching operation, with Euro profile half cylinder and three keys / Spring return on one side (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054245	silver-coloured	75 x 75 x 11 mm	Flush-mounted installation
Key switch SCT 221	One-sided spring return, without euro profile half cylinder / Spring return on one side (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054532	silver-coloured	75 x 75 x 50 mm	Surface-mounted installation

TPS

Keypad programme switch for setting the mode of operation for automatic doors



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
Keypad programme switch TPS	with 2 control keys, LED display, coded fault display, IP rating IP40 / suitable for switch ranges with 55x55mm switch insert	113231	alpine white	80 x 80 x 11 mm	24 V DC
Keypad programme switch TPS-KDT	with 2 control keys, LED display, coded fault display, IP rating IP40 / suitable for switch ranges with 55x55mm switch insert	126582	alpine white	80 x 80 x 11 mm	24 V DC
Keypad programme switch TPS and key switch SCT	in combined double frame without Euro profile half cylinder	113232	alpine white	80 x 152 x 11 mm	24 V DC

WRM-24


Receiving module for activating automatic doors and window drives with 24 V DC



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
WRM-24 receiving module	52 x 47 x 23 mm (W x H x D), for installation in a standard flush-mounted box / 24 V DC operating voltage, pulse mode or pulse and permanent mode	131213	black	52 x 52 x 47 x 23 mm	24 V DC

WRM-24B

Receiving module for activating automatic doors and window drives with 24 V DC



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
WRM-24B Receiving module	130 x 80 x 35 mm (W x H x D), for surface installation with protection rating IP54 / 24 V DC operating voltage, pulse mode or pulse and permanent mode	131214	white	130 x 130 x 80 x 35 mm	24 V DC

Slimdrive SLT



WTH

Remote control for activating GEZE automatic doors and window drives via the GEZE wireless programme

Name	Description	Ident-No.	Dimensions	Operating voltage	Type of installation
WTH-2 Remote control 2 channels	with wall fixing and IP rating IP54	131210	78 x 51 x 15 mm	12 V DC	Wall installation
WTH-4 Remote control 4 channels	with wall fixing and IP rating IP54	131211	78 x 51 x 15 mm	12 V DC	Wall installation
WTH-1 Remote control 1 channel	with wall fixing and IP rating IP54	131209	78 x 51 x 15 mm	12 V DC	Wall installation

AS 500

Manual trigger switch for the manual release of electrically controlled hold-open devices



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
AS 500 manual trigger switch	for the manual release of electrically controlled hold-open devices including terminating resistor for line monitoring	116266	alpine white/red	80 x 80 x 9 mm	24 V DC
AS 500 manual trigger switch, glass	for the manual release of electrically controlled hold-open devices including terminating resistor for line monitoring, glass pane and 5 interchangeable labels	120880	alpine white/red	80 x 80 x 21 mm	24 V DC