

Product data sheet RWA K 600 T



Retractable arm drive for air intake systems for installation on doors

AREAS OF APPLICATION

- ightarrow Use in the supply air system where large opening angles are required
- → Single and double leaf smoke and heat extraction fresh air doors
- → Installation on the hinge or opposite hinge side

RWAK 600 T



PRODUCT FEATURES

- → 90° door opening in less than 60 seconds
- → Powerful drive with high torque
- → Connection cable easy to replace by means of plug
- → Integrated status contact for electric strike control unit or feedback signals
- → Door remains freely accessible due to the freely positioned activation of the lever by means of a pressure roller

TECHNICAL DATA

Productname	RWA K 600 T			
Dimensions	421 x 40 x 56 mm			
Compressive force	600 N			
Operating voltage	24 V DC			
Current consumption	1.4 A			
Residual ripple (max.)	20 %			
Duty rating	30 %			
Connection cable length	5 m			
Special length of power supply cable	10 m			
min. core dimension	0.5 mm ²			
Number of cables	5 cores			
Temperature range	-5°C+75°C			
IP rating	IP32			
protection rating	III			
Syncro function	Yes			
Adjustable opening speed (ventilation)	Yes			
Additional locking available	Yes			
Type of additional locking mechanism	Locking drive			
End position cut-off extended	Internal path sensor			
End position cut-off retracted	Internal path sensor			
Overload cut-off	Yes			
Number synchronisation drive units	2			

VARIANTS / ORDER INFO

Description	Description	ldent- No.	Colour	Dimensions	Operating voltage
RWA K 600 T		130059	EV1	421 x 40 x 56 mm	24 V DC
RWA K 600 T 2-leaf with closing sequence - special version	Can be configured: Fixed/active leaf, start-up delay, status contact, colour	137450	acc. to RAL	421 x 40 x 56 mm	24 V DC

RWAK 600 T



Description	Description	ldent- No.	Colour	Dimensions	Operating voltage
RWA K 600 T 2-leaf with door closing sequence selector		137449	EV1	421 x 40 x 56 mm	24 V DC
RWA K 600 T - special version	Can be configured: Version master/slave, status contact, colour, opening angle, free programming	130060	acc. to RAL	421 x 40 x 56 mm	24 V DC

ACCESSORIES

BRACKET G FOR RWA K 600 *

Mounting bracket for K 600 retractable arm drive



CONSOLE R FOR RWA K 600 *

Mounting bracket for K 600 retractable arm drive



BRACKET T FOR RWA K 600

Mounting bracket for K 600 retractable arm drive



Description	Ident-No.	Colour	Dimensions	Length
Console T for RWA K 600	140505	acc. to RAL	100 x 75 x 50 mm	100 mm

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.