

<b>Technology/Operation</b>	
<b>Measuring Principle</b>	Underwater ultrasonic sludge level measurement
<b>Measuring Range</b>	0.6-12 metres (2-39 ft)
<b>Performance</b>	
<b>Accuracy</b>	+/- 0.03m
<b>Resolution</b>	0.003m
<b>Response Rate</b>	Fully adjustable
<b>Echo Processing</b>	Sophisticated algorithms using 32 bit Digital Signal Processing
<b>Power Supply</b>	115/230 VAC
<b>Outputs and Communications</b>	
<b>Analogue</b>	1 4-20mA output, 750Ω
<b>Digital</b>	4 SPDT programmable relays, 5A @ 230 VAC (2 user programmable, 1 purge control, 1 LOE)
<b>Telemetry (optional)</b>	Site specific, range up to 2 miles (3km)
<b>Communication</b>	Standard RS232, optional RS485
<b>Programming</b>	
<b>User Interface</b>	3-button keypad with menu driven programming
<b>Echo Profile</b>	Graphical LCD display of raw echo profile
<b>Programming Security</b>	Password protected
<b>Data Integrity</b>	Non-volatile RAM
<b>Environment</b>	
<b>Temperature Range (electronics)</b>	-20°C to +60°C (-4°F to +140°F)
<b>Outdoor Rating</b>	IP65, UL Approved Enclosure with UV Protected Clear Lid
<b>Design</b>	
<b>Dimensions</b>	280 x 219 x 156 mm (11.0 x 8.6 x 6.1 inch)
<b>Cable Entry</b>	8 Available for Wall Mount: 1xM12, 1xPG9, 5xM20 bottom row
<b>Mounting</b>	2 Fixed Holes & 1 Hanging Hole, Optional DIN Rail Tabs
<b>Enclosure Material</b>	Polycarbonate, flmae resistant to UL94-5V
<b>Weight</b>	Approximately 1.4Kg (3 lbs)
<b>Transducer Specifications</b>	
<b>Standard Cable Length</b>	20 metres (66 ft), optional custom lengths
<b>Cable Specification</b>	Shielded Coax Cable
<b>Maximum Cable Run</b>	50 metres (150 ft)
<b>Temperature Range (Transducer)</b>	-40°C to +95°C (-40°F to +200°F)
<b>Dimensions</b>	50mm diameter x 75mm length (2 x 3 inches)
<b>Mounting</b>	1 inch NPT Male Thread
<b>Material</b>	PVC Housing, IP68 Rating



<b>Beam Angle &amp; Frequency</b>	6° total, 12. MHz
<b>Cleaning</b>	Hose Tail Air Pipe Connector for Air Purge
<b>Cleaning Frequency</b>	User-programmable, 1-720 minutes (12 hours)
<b>Weight</b>	Approximately 0.5 Kg (1 lbs)