

Technical Spec Sheet

SG55 SOLID ALUMINIUM ROLLER SHUTTER

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

Curtain construction and Weight

55mm x 13.5mm twin walled solid extruded aluminium lath.
Weight 8.44kg m².

Bottom Bar and Guides

The bottom bar is 60mm x 8mm twin walled extruded aluminium with bottom rubber.

Guides for a 205mm box are 66mm x 27mm Extruded Aluminium construction including brush strips.

Guides for 250mm, 300mm & 360mm box are 75mm x 27mm Extruded Aluminium construction including brush strips.

Shutter Hood

Die cast aluminium end plates with a preformed 2-piece aluminium hood.
Shutter hood ranges from 205mm to 250mm for a manual shutter and 205mm to 360mm for a motorised shutter, subject to size of the shutter.

Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.
Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake.

Finishes/ Colour

Polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as standard or to any stocked BS or RAL colour at additional cost.

Applications

Medium to high level of security for retail and commercial premises. Ideal for larger widths.

Suitable for internal or external use.

SG55 Solid Aluminium

