

**BODPAVE™ 85 cellular  
 porous pavers with  
 castellated cells**

 T: +44 (0)1621 874200  
 F: +44 (0)1621 874299

**Product Data Sheet**

Issue: 01 Date: 20.07.12

Characteristics	Black	Green*	Natural
Load-bearing capacity (filled)	400 t/m <sup>2</sup>		
Crush resistance (unfilled)	<250t		
Connection & locking type	Overlapping edge loop & cell connection with integral, self-locking, snap-fit clips		
Basal support & anti shear	Integral 35mm long ground spikes (18/paver) with cross & T section		
Dimensions	500mm x 500mm x 50mm deep plus 35mm long ground spike		
Cell wall thickness	2.5mm - 4.4mm		
Nominal internal cell dimensions	67mm (cruciform) & 46mm (round)		
% open cell	92% (top)/75% (base)		
Quantity per m <sup>2</sup>	4 pavers		
Weight	1.56kg (6.24kg/m <sup>2</sup> )		
Polymer	Recycled	High density	
Chemical resistance	Excellent		
UV resistance	High		
Toxicity	Non toxic		



\* Please note that when using recycled HDPE it is difficult to maintain colour consistency across single green pavers, and from one green paver to another.

In addition, virgin polymer may be used to manufacture the green pavers when recycled green HDPE is in short supply.

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.