

cantorodado

by Stimulo



Petra 1

Modeladas sin aristas como si la misma naturaleza las hubiera erosionado.

Modelades sense arestes com si la mateixa natura les hagués erosionat.

Rounded design, as if eroded by nature itself.

Modelé sans bords comme si la nature avait érodé.

Modellate senza bordi, come se la natura stessa le avesse eroso.

Kantenfrei gestaltet, wie von der Natur selbst geformt.

TECHNICAL CHARACTERISTIC

Manufactured product technical features are validated by officially approved laboratory tests.

▪ **Freeze resistance** 25 cycles of ice (-25°C) / defrosting (+15°C) without fissures, layers nor scaling having occurred.

▪ **Flexural and compressive strength** (UNE EN 1015-11 (196-1):

Flexural: 78 kgf/cm² (average value among the different standard colours)

Compressive: 440 Kp/cm² (average value among the different standard colours)

Colours

> Standard colours [without coloured pigments] grey [1] | white [2] | ochre [3]

> Other colours (with coloured pigments) on order. Percentage increase according the colour characteristics and the order request.

Finished

Scoured.

Anti-graffiti superficial treatment optional.

Water repellents treatment superficial optional.


Manufactured in Architectural Cement




cantorodado 125 | 540 kg | 216 L

cantorodado 200 | 1.060 kg | 742 L

cantorodado 235 | 1.340 kg | 1.087 L



cantorodado 100 | 605 kg | 146 L



cantorodado 65 | 440 kg | 57 L

