Product Specification Document

# Aqua Control

Yosemite Series Waterfall Pump System





## Description;

This 7.5HP to 40HP product line is built using turbine pumps designed to produce very high flow (4,542LPM Max.) with higher head up to 45m or more.

### **Key Features;**

UV resistant flex hose (reinforced for pressure and durability), lighting options available, easy clean, high strength suction screens, electrical quick disconnect, low resistance non-spring valve design to prevent backflow.

Motor Rating (HP)	Power Rating (KW)	Flow rates in LPM at varying head*						
		7.5m	10.5m	13.7m	16.7m	19.8m	22.8m	24.3m
7.5	8	-	-	1636	909	-	-	-
10	11	-	-	2727	2386	2045	1545	1272
15	16	-	-	-	2818	2500	2136	1909
Motor Rating	Power Rating	Flow rates in LPM at varying head*						
(HP)	(KW)	18.2m	22.8m	27.4m	32m	36.5m	41m	47.2m
20	21	4136	3182	1682	-	-	-	-
25	26	-	-	3455	1909	-	-	-
30	31	-	-	4818	4046	3000	-	-

### Model Specifications;

\*Head is the Height that a pump will lift water at the selected LPM

#### Warranty;

This waterfall system is covered by a 3-year parts warranty and 2-year return to base labour warranty. The warranty does not cover serviceable parts after two years. Any damage caused by poor maintenance, careless handling, misuse, abuse or freezing will not be covered under warranty. Modification or repair by an unauthorised repair facility will void the warranty.



Heathland Group Limited, 8 Thorpe Road Norwich, Norfolk, NR1 1RY Tel: 01692 671951 Email: info@heathlandgroup.co.uk Company Registration: 11418403

