

## ROSTY Bench

## LRO2



The picture is only illustrative, it may not exactly match the product described.

Product description	Construction is made of steel weldment from sheet metal burn parts 10 mm thick. Wooden laths are attached to the steel construction with screws. The seat is made up in total of 53 lamellas 68 x 42 mm (70 x 40 mm for tropical wood) of various lengths that are fixed together in one board through stainless threaded rods M12 and spacers. An asymmetric square hole for the trunk of the tree is placed in the seat.
Material	Construction: steel grade 11 Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood <a href="#">DOWNLOAD PDF SAMPLER &gt;</a>
Surface treatment	Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium). Other RAL shades according to RAL sampler on request only. Spruce – two-layer impregnation and lacquer mixed with water with beeswax Tropical wood – treated with teak oil Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Dimensions	2840×1386×420 mm / 550 kg
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 100 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

