

BOROLA Bench

LBL1



The picture is only illustrative, it may not exactly match the product described.

Product description	Bench with aluminium alloy sides. 10 wooden laths of rectangular cross-section and 6 laths of atypical arched cross-section with radius R 80 mm are carried by bench sides. They are attached to the sides with stainless steel screws. The seat and backrest laths are interconnected by a reinforcing steel belt.
Material	Construction: aluminium alloy, sheet metal blast 4 mm thick Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood <a href="#">DOWNLOAD PDF SAMPLER &gt;</a>
Surface treatment	Natural aluminium shade optionally with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium). Other RAL shades according to RAL sampler on request only. Spruce – two-layer impregnation and lacquer mixed with water with beeswax Tropical wood – treated with teak oil Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Dimensions	1800×734×784 mm
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

