

# Companionway Ladder



COMPANIONWAY LADDER - Complying with the recommendations of BS 5395: Part 3

## SPECIFICATIONS - Aluminium

Stiles: Aluminium
Punched aluminium treads
Brackets from 50 x 10mm alloy bar
Fixings in stainless steel
All alloy in mill finish
Grabrail height: 300mm (nom)
Overall ladder width: 600mm
Ladder angle: 75 degree (nom)

### ALUMINIUM COMPANIONWAY LADDER

Type	Size	Approx Weights (kg)
BL-COMPA1	Up to 1.5m	Up to 32
BL-COMPA2	Above 1.5 - 2.0m	32 - 37
BL-COMPA3	Above 2.0 - 2.5m	37 - 41
BL-COMPA4	Above 2.5 - 3.0m	41 - 46
BL-COMPAS	Special sizes available on request	

## SPECIFICATIONS - Mild Steel

Stiles: Mild steel
Punched mild steel treads
Brackets from 50 x 10mm flat bar
Fixings in stainless steel
Finish: Galvanised
Grabrail height: 300mm (nom)
Overall ladder width: 600mm
Ladder angle: 75 degree (nom)

### MILD STEEL COMPANIONWAY LADDER

Type	Size	Approx Weights (kg)
BL-COMPS1	Up to 1.5m	Up to 88
BL-COMPS2	Above 1.5 - 2.0m	88 - 101
BL-COMPS3	Above 2.0 - 2.5m	101 - 114
BL-COMPS4	Above 2.5 - 3.0m	114 - 128
BL-COMPSS	Special sizes available on request	



Bilco products are designed and fabricated to consistently high quality standards to ensure complete customer satisfaction.



THE WORLDWIDE SOURCE FOR SPECIALITY ACCESS PRODUCTS

Tel: 01284 701696 Fax: 01284 702531  
Email: bilcouk@bilco.com www.bilcouk.com

