

SLIDING CANTILEVERED GATE



The popular Sliding Cantilevered Gate, which secures apertures up to 10m.

- Standard height: 2400mm, Max height 5000mm
- Full Welded Construction
- Choice of infills including security weldmesh, bar and weldmesh, sheet, decorative & wood.
- Bespoke manufacturing

BENEFITS & FEATURES

- Cantilevered Gate; requires no ground track or support across the roadway.
- The gateleaf is supported by a main bottom beam, which slides 100mm above the road surface.
- The balance is provided by a unique enclosed runback track, which enables the gate to be fully projected across the roadway without tipping.
- Electronic control motor drive unit, 100% duty rated

OPERATING SPEED

- Typical operating speeds of 200-250mm/second* depending on configuration

OPTIONS

- Disengaging box – manual override
- 100/200mm Traffic Light System
- Can be interfaced to any access control systems

SAFETY

- Vehicle detector loops
- Safety photocell beams and ultra-sonic sensors
- Safety edges
- Signage, audible alarms and flashing beacons

CIVIL REQUIREMENTS

Gate leaf foundation

L: 300mm + Runback length

W: 1000mm

D: 300mm

Receptor post foundations

L: 600mm

W: 1000mm

D: 300mm

Note: Power and control wiring ducts to be incorporated into foundations


- **Minimum length of runback track:**

For gate apertures of 8m

Runback = Aperture x 1.5

ELECTRICAL REQUIREMENTS *

- 6 amp, 3 wire, 230v, 50hz, single phase supply



Applications: The popular Sliding Gate, installed on many locations Nationwide and Internationally, including both commercial and industrial sites.

* This is subject to a risk assessment to ensure the automatic equipment complies to BS EN 12453