STRATACELL

PRODUCT GUIDE



Soil Structure System

Includes:

- Product information sheets
- Technical data sheet





StrataCell

SOIL STRUCTURE SYSTEM

Designed to highly advanced engineering specifications to support greater vertical loads, **StrataCell** brings tree-root systems closer to pavement surfaces. Engineers have calculated that, with only 300mm of granular pavement depth, a **StrataCell** matrix can support maximum traffic loads.

Load bearing Geonet is laid over the top of the StrataCell structure to prevent the ingress of the surface sub-base into the rooting area.



Large void spaces between columns





BENEFITS

- Integrated matrix means modules are simple and fast to click together.
- In excess of 94% of total soil volume is available for tree-root growth.
- Generously designed apertures permit common conduits, service pipes and aeration systems.
- Significant volume reduction for freight and lower transport costs.
- Reduced installation costs.
- Constructed from 100% recycled material.
- Designed to support enormous vertical as well as lateral loads.
- Excellent modular strength.

Important - Please read these instructions fully before starting assembly For further help telephone our technical helpline on 01424 433233



StrataCell

SOIL STRUCTURE SYSTEM



Load bearing deck for spanning shared utility trench



Interstacked for shipping

Typical Installation Specification

Please contact GreenBlue Urban for full installation specification

Compatible products

- Root management
- Underground root ball guying
- Tree grilles and guards
- Porous resin bound gravel



Easy clip together matrix design

StrataCell Module specification

Description	Recycled plastic rigid skeletal interlocking octagonal structure		
Material	Advanced glass reinforced polymer		
Dimensions	500mm x 500mm x 250mm		
Code	Description	Loading Capacity	
	1	5 1 7	
GLSCMA	· StrataCell 60 Series Module	550kpa	
GLSCMA GLSCM30A	StrataCell 60 Series Module StrataCell 30 Series Module	550kpa 260kpa	



SOIL STRUCTURE SYSTEM

TYPE

Large structural soil support module

CODE

GLSCMA 500mm x 500mm x 250mm

MATERIAL

Recycled glass reinforced polypropylene

LOAD BEARING CAPACITY

550kPa vertical load

FINISH

Natural

COLOUR

Black

WEIGHT

3.86kgs

VOID/SOIL

94%







SOIL STRUCTURE SYSTEM

TYPE

Large structural soil support module

CODE

GLSCM30A 500mm x 500mm x 250mm

MATERIAL

Recycled polypropylene

LOAD BEARING CAPACITY

260kPa vertical load

FINISH

Natural

COLOUR

Black

WEIGHT

3.86kgs

VOID/SOIL

94%







Load Bearing Geonet DATASHEET



Raw Material

Grid Nonwoven Coating	PET 150 g/m ² PP Polymer				
Weight					
EN ISO 9864	~420	g/m ²			
Ultimate tensile strength					
EN ISO 10.319 Longitudinal Transversal	≥ 40 ≥ 40	kN/m kN/m			
Strain at nominal tensile strength					
EN ISO 10.319 Longitudinal Transversal	≥ 12.5 ≥ 12.5	% %			

Mesh size of the geogrid

	25 x 25	mm		
Opening size				
EN ISO 12956	~0,10	mm		
Opening size				
EN ISO 11058	~75	x 10-3 m/s		
Standard Dimension				
Width x Length	1m	100m		

No responsibility is accepted for any change in product properties due to environmental influences and / or improper application or handling. Rights are reserved to modify the product to effect improvements.

