

▶ Industrial Roof Access



Features and Benefits

- ▶ Suitable for fragile roofs
- ▶ Adjustable to pitches up to 30 degrees (Valley-Walk - 85 degrees)
- ▶ Easily transportable
- ▶ Simple and quick to use

Our Industrial roof access equipment is intended to simplify short duration roof work.

Designed to overcome the challenges with working on fragile roofs, and provide the user with a safe working position for skin maintenance, inspection, cleaning or re-sealing work.

Board-Walk - Is an open mesh walkway that allows access from eaves to ridge whilst spreading the load on support battens.

Roof-Walk - A fully guarded rolling work platform mounted on twin tracks to enable you to move up and down the roof.

Valley-Walk - Is a mobile walking frame for one or two persons designed to aid access along valley gutters and provides mobile roof cover.



Short duration maintenance



Glazed roof access



Northlight valley access

Technical Specification

Board-Walk

▶ Length	4 m sections
▶ Walkway width	600 mm
▶ Material	High grade aluminium
▶ Total weight	28 kg

Compliance

- ▶ EN12811

Roof-Walk

▶ Track length	8 m (2 x 4 m sections)
▶ Platform length	4.6 m
▶ Platform width	620 mm
▶ Platform weight	200 kg
▶ Total weight (including track)	361 kg
▶ Material	High grade aluminium

Compliance

- ▶ EN12811

Valley-Walk

▶ Length	2100 mm
▶ Width	1950 mm
▶ Material	High grade aluminium
▶ Total weight	24 kg

Compliance

- ▶ EN12811

Board-Walk is easily portable and the mesh walkway allows for full visibility and all weather use. The 4 m sections are easily linked and an optional handrail is available. It also has an integral full length work positioning line.

Roof-Walk's rolling platform is available as 4.6 m as standard, although it can also be made as a 2.5 m platform, and runs up and down twin modular 4 m linking track sections that are fitted with safety mesh and support battens.

Valley-Walk is easily assembled and gives up to 2 workers complete safety whilst working in a valley. There are cushioned outriggers for comfort which are filled with a safety mesh, and it can be used to transport a light payload. The Valley-Walk is suitable for typical symmetrical valleys, but also fully adjustable to suit asymmetrical designs such as northern lights.

▶ **Free demonstrations available on all our products.**