

Resin Bound Gravel is DCM Surface's premier decorative gravel surface.

Available in a range of colours and blends, the gravel surface is extremely hard wearing and provides visually stunning finishes. Bound Gravel is the ideal surface for driveways, pathways and walkways.

Resin Bound Gravel is applied using your choice of coloured gravel aggregate, binding them together with resin to form a permeable bound gravel system which is SuD compliant.

DCM are always the first company I think of when surfacing works are required.

> Over the years my experience with DCM has always been one of high quality. From the start to the end of each project - the professionalism of the Contracts teams and site operatives is exceptional throughout.

Project Manager, Ardmore

### **Key Specifications**

- · Incorporate logos / designs
- Range of colours available
- Permeable / SuDS compliant
- · Durable and hard wearing
- Visually appealing

## RECOMMENDED BUILD UP TO CREATE A PERMEABLE SURFACE



- 3 100-300mm MOT type 1 /3 dependent on ground conditions
- 4 Geotextile
- 5 Edge options: Concrete, Aluminium
- \*Depth of resin gravel will vary for vehicle use

T. +44 (0)1772 440340 E. info@dcmsurfaces.com

# **BOUND GRAVEL**



<sup>\*</sup>Additional colours available on request

#### **Base**

The base must be dry and of sound construction.

SURFACE DEPTH	CONCRETE	MACADAM	CONIPAVE	FLAGS	SOIL / GRASS	MOT TYPE 1
16mm - Pedestrian	<b>✓</b>	✓	×	×	×	×
18mm - Pedestrian	<b>√</b>	✓	<b>✓</b>	*	×	×
18-20mm - Vehicles	<b>✓</b>	✓	×	×	×	×
24mm+ - HGV / Tree Pits	<b>√</b>	<b>√</b>	×	×	×	✓

<sup>\*</sup> May require fibre glass mesh prior to application of gravel

## **Bound Gravel Technical Data**

TECHNICAL DATA	VALUE
Material	Resin Bound Aggregate 7% min binder content
Curing Period	12 hours - Pedestrian Use 24-48 hours - Vehicle Use (weather dependent)



