

Climbing equipment

(technical specification)

J57011



1- The 125mm diameter posts are made of lacquered galvanised steel. The two-tone grey grained finish has a slightly undulating surface for increased scratch resistance. The caps are made of injection moulded polyamide.



2- The 125mm round posts are made of laminated timber, which have not been treated with chrome or arsenic. Splinter-free, the laminate provides great strength and dimensional stability. The posts are protected from wear and tear caused by fungi and insects.



3- Galvanised, painted steel posts 95x95mm, guarantee long term durability.



4- The caps are made of rotary moulded polyethylene.



5- Injection moulded polyamide fixings are made of lacquered galvanised steel.



6- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.





7- The 16mm diameter ropes are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



8- The net fittings are made of polyamide.

The fittings are composed of two distinct parts for ease of maintenance of individual strands.



9- The platform is made from a 12.5mm thick textured and non-slip compact material (HPL).



10-The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



11-The sliding surface is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.

The sides are made from a 13mm thick compact material (HPL).



12-The climbing holds are made of polyamide for its strength and rigidity.



13-The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

