

	RANGE FLAGS AND PAVERS			SPACER		CHAMFER		
					a subbase and the	Breccia, Martello,	Perlano	Lavaro
	Width	Length	Thickness			Liscio and Sabio 1mm	3mm	5mm
			60mm THICK					
	150	300	60			•	•	
	200	200	60	•		•	•	
	200	300	60	•		•	•	•
	210	210	60		•	•		•
	300	300	60	é		•	•	
	000	000	70mm THICK					
	80	240	70	•		•		
		2.10	80mm THICK					
	50	200	80	•		•	•	
	60	240	80	÷		•		
	69	210	80		•	•		•
	100	100	80	•		•		
	100	200	80	•		•		•
	105	210	80	•	•	•	•	•
	105	315	80	•	-	•	-	-
	110	330	80	•		•		•
	125	250	80	•		•		•
	125	150	80	•		•	•	
							•	
	150	200	80	•		•		
	150	300	80	•		•	•	
	150	400	80	•		•		
	200	200	80	•		•	•	•
	200	300	80	•		•	•	
	200	400	80	•		•	•	
	200	600	80			•		
	210	210	80		•	•		•
	300	300	80	•		•	•	
	400	400	80	•		•	•	
	500	500	80	•		•	•	
	600	600	80	•		•	•	
			90mm THICK					
	900	900	90		•	•		
			100mm THICK					
	100	300	100	•		•		
	105	420	100		•		•	•
	110	330	100	•		•		•
	150	300	100	•		•	•	
	150	600	100	•		•		
	200	200	100	•		•	•	•
	200	300	100	•		•	•	
	200	400	100	•		•	•	
	200	600	100	•		•		
	300	300	100	•		•	•	
	300	600	100	•		•		
	300	900	100	•			•	
	500	500	100	•		•	•	
	500	1000	100	•		•		
	600	900	100	•		•		
	700	500	100	•		•		
	, 50	000	120mm THICK			-		
	900	900	120		•	•		
	1000	1000	120		•	•		
	1000	1000	140mm THICK		-	-		
	1000	1000	1401111 1110		•		•	
Perlan		1000	140		-	I	-	
renam		200	50/60/70/80				•	
	200	200						
	150	300	50/60/70/80				•	
	300	300	50/60/70/80				•	
	200	400	50/60/70/80				•	
	400	400	50/60/70/80				•	
	400 500	600 500	50/60/70/80 50/60/70/80				•	
		500	5U/6U//(U/80)		1		•	

Head Office

Ashworth House, Deakins Business Park, Egerton, Bolton BL7 9RP T 01204 590666 F 01204 590620 E eng@hardscape.co.uk

Southern Office Unit 25, Long Marston Industrial Estate, Long Marston, Stratford Upon Avon CV37 8QR T 01789 721012 F 01789 721041 E enq@hardscape.co.uk

ellen

Brave landscaping for those who are streets ahead of the rest...

HARDSCAPE

www.hardscape.co.uk



Middlesbrough College, Middlehaven

The ingenious modular concrete paving range from Hardscape hosts a new generation of inspirational paving products that combine the efficiency and integrity of 10% recyclable concrete paving with cement-bonded top layered natural stone aggregate.

Manufactured in Holland, it is available in a variety of colours, finishes and sizes and offers ingenious solutions to hard landscaping schemes.

Sustainable

The Kellen factory has processes in place to reduce dust output into the atmosphere and to save energy and therefore REDUCE CARBON emissions Recycled water is used in the manufacturing process and raw materials are transported for 90% of their journey by water. As a standard, at least 10% of the raw materials used in the backing layer are from recyclable sources. All products carry a CE mark. As an option products can also be supplied with the Dutch Eco Label (Milieukeur) which guarantees the use of certified recycled building materials for at least 10% in the backing layer.

Sizes

Sizes range from 100x100x80mm to 1000x1000x140mm and can be easily combined with various kerbs and edgings with flexible laying in pedestrian areas and zones with vehicular traffic.

Standards

All products conform to the EN standards 1338, 1339 and 1340 with high quality classes for size tolerance, strength, resistance to freeze/thaw and wear. The material can be laid on sand as a flexible paving system as opposed to laying on cementitious bedding mortars providing a cost effective paved scheme. The final result provides a granite aggregate surface offering a real alternative to natural stone products when circumstances require.

Laying

The product can be machine laid with bespoke machinery that Hardscape have helped develop. Hardscape also recommend using a selected kiln-dried 'silver' sand to complete the final laying for best looking results when using the flexible jointing system from the Kellen range of products.



Cank Street, Leicester

Haletop,

Milngavie

Thomas More Square, Londo





Breccia	alpi	ambrogio
giallo	grigio	maron
tagenta A	tagenta B	tagenta C
Lavaro	geel	grijs
oranje	paars	rood
Liscio	alpi	ambrogio

gow

DISCLAIMER: Due to variations in the printing process this colour swatch represents an approximate guide to Hardscape colour-types of Kellen within this selective range. Please request individual samples to appreciate and confirm colour selection.



Specials

Kellen offers a complementary range of kerbs, planters and steps to form a coherent public space creating its own unique identity. These products are available in 5 standard colours of the Lavaro finish only, including bespoke items which are available upon request and consultation.



Kerbs

Hardscape has selected a range of kerbs, each having a different way of separating traffic, whether it is visual guidance or physical by height. Each kerb-model offers a wide choice of radii, angles and corners, as well as dropping kerbs. Kellen kerbs are in compliance with EN-1340.

Half Battered Kerbs





Flush Kerbs

120x250x1000

150x250x1000

Splayed Kerbs

120x250x1000 200x200x1000

200x250x1000

Planters

Kellen planters are available in different sizes and bespoke. Whether used for grass and tree borders or as retaining element to accentuate heights.







Steps

With Kellen steps it is possible to connect different levels in accordance with the paving that is used.













