brassware

sensorflow 2 I

Sensorflow 21 range offers every type of sensing brassware. Basin or wall mounted with integral sensor and tubular wall spouts with remote sensor. Shower and urinal flushing controls.

Mains powered (transformer) with option to link up to 5 multi box units per main unit and independent battery powered units.

- Commercial use
- Hygienic "no touch operation"
- Anti vandal
- Chromium plated
- DDA compliant



Illustrated

A4178AA Sensorflow 21 wall-spout electronic, built-in sensor 150mm spout, mains

Weight


1.8kg


Options

A4179AA Sensorflow 21 wall-spout electronic, built-in sensor 150mm spout, multi-box (up to 5 per A4178AA) A4125AA Sensorflow 21 wall-spout electronic, built-in sensor 150mm spout, battery

Special notes

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device











9:3:25F

brassware

sensorflow 2 I

Sensorflow 21 range offers every type of sensing brassware. Basin or wall mounted with integral sensor and tubular wall spouts with remote sensor. Shower and urinal flushing controls.


Mains powered (transformer) with option to link up to 5 multi box units per main unit and independent battery powered units.

- Commercial use
- Hygienic "no touch operation"
- Anti vandal
- Chromium plated
- DDA compliant



min 350 - 27 --- 150 Ø55 35 max

A4180



Illustrated

A4180AA Sensorflow 21 tubular 150mm wall mounted spout with separate sensor, mains

Weight

1.8kg

Options

A4181AA Sensorflow 21 tubular 150mm wall mounted spout with separate sensor - multibox (up to 5 per A4180AA) A4126AA Sensorflow 21 tubular 150mm wall mounted spout with

separate sensor battery

A4183AA Sensorflow 21 tubular 230mm wall mounted spout with separate sensor - mains A4184AA Sensorflow 21 tubular 230mm wall mounted spout with separate sensor - multibox (up to 5 per A4183AA) A4182AA Sensorflow 21 tubular 230mm wall mounted spout with

separate sensor battery

Special notes

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device





