IMPRESSIONS RANGE

INSPIRATIONAL NATURAL SURFACES































IMPRESSIONS RANGE

INSPIRATIONAL NATURAL SURFACES

THE SUSTAINABLE SOLUTION

RMS has extensive experience as a contractor in providing specialist decorative finishes. High quality binder systems provide a durable treatment as an alternative to asphalt, brick paviors, paving slabs and concrete. Depending upon site requirements either Impressions Bindcoat or Impressions Bondcoat is specified to achieve the desired finish. A wide range of coloured chippings ensures a decorative surface appearance to suit all tastes and applications.

TYPICAL APPLICATIONS FOR THIS TYPE **OF SURFACE:**

- Private housing driveways and parking
 - **Footpaths**
 - Stately homes
 - Parks and gardens
 - **Architectural features**
 - Areas requiring colour delineation
 - Cycle tracks
 - Car parks
 - Tow paths





NATIONAL TRUST AND STATELY HOMES

- Roadways, paths, picnic areas and car parks
- In keeping with historical feel and profile
- Long lasting modern day protection
- Used at Dunham Massey, Tatton Park, Berington Hall, Lyme Park and Tabley Hall



DRIVEWAYS AND CAR PARKS

- Durable
- Aesthetically pleasing with a degree of personalisation
- Wide range of colours
- Low Maintenance
- Adds value



PARKS AND GARDENS

- Decorative finish to complement environment
- Hard wearing
- Natural aggregate

- Safe walking texture
- Used at Telford Town Park, Arley Hall Park and Gardens



CYCLE TRACKS

- Colour delineation
- Cost effective
- Renews and adds value
- Enhanced surface texture



TOWPATHS

- Ideal finish for reconstucted towpaths
- Historical sympathy and nostalgia
- Extends life of the path
- Endorsed by British Waterways





PREPARATION

Can be laid on a variety of existing or new sufaces, e.g. compacted granular material, macadam, asphalt, concrete, planings, previously dressed surfaces, bitumen, ash and recycled aggregates, It requires:

- A clean sound and even surface
- Formed profile or a natural existing profile

DESIGN AND PROCESS

- All sites inspected and designed offering single or multi layered treatment
- Process and application will be carried out as per guidance of Road Note 39 6th Edition
- This process is supported by TAIT (Type Approval Installation Trial)
- Laid by specialist experienced operatives with CSCS certificate (Construction Skills Certification Scheme)
- RMS offer a detailed no commitment survey prior to installation

PLANT AND EQUIPMENT

- Unique specialist equipment designed and built by RMS
- Purpose built equipment designed to reach areas of restricted access

TECHNICAL DATA

- Aggregate nominal sizes: 3mm, 6mm, 10mm, 14mm
- Binder: K170, Intermediate Polymer Emulsion, Premium Polymer Emulsion, Clear Binder, Epoxy
- Typical aggregate spread rates per layer: 7-16kg per m2
- Average coverage rate conforms to EN 12272-1

QUALITY ASSURANCE

Accredited to BS EN ISO 9001 2000 and National Highways Sector Scheme 13a

GUARANTEE

- All works fully guaranteed
- RMS established 1947















COLOURS AVAILABLE



COTSWOLD **MERCASTON STAFFORDSHIRE CRIGGION CLOBURN**

