Installation instructions

Dish roundabout SWD100 Sheet 1 of 3 Rev 11

Sutcliffe Play




The site must be level to maintain critical dimensions.

Foundation detail for loose fill surfacing

Play level Soose Fill Soose

Foundation detail for wet pour/tiles



Installation instructions

Dish roundabout SWD100 Sheet 2 of 3 Rev 11

Installation procedure

- Plan the final position of the play equipment ensuring that 1. there is sufficient space*.
- 2. Excavate the foundation hole in accordance with the plan**.
- Place the ground fixing in the foundation hole, ensure it is level and at the required depth. Fill with concrete.
- When the concrete has set (2 3 days) fit the Dish roundabout 4. frame.
- Do not allow the equipment to be used until the concrete 5. has set (2 - 3 days) and the required safety surface has been installed.
- 6. Check if all the fixing bolts are tight.
- Follow the Maintenance Instructions provided. 7.
 - * Care should be taken when installing the product, to reduce the hazard for the user.
 - ** Care should be taken if conditions aren't normal.

Space requirements to EN1176

- Area of safety surface 23M2 based on 2.1M from the 1. extremity of the equipment.
- 2. Perimeter of safety surface 17.5M.
- HIC 1M.

Parts supplied

No Description Qtv Stock Code Dish roundabout 1.


Ground fixing 2. 1 **SWD115**

Set of fixings:-3.

M12 x 25 Screw MCS406

Required tools for installation

8mm Allen Key Tape measure Spirit level Digging equipment



ANN SUCCESTIFE POR SUCCESTIFE PROPERTY CO. LIK

Maintenance instructions

Dish roundabout SWD100 Sheet 3 of 3 Rev 11

NOTE

The warranty is invalidated if these instructions are not

SuiclifiePlai Recommended regular inspection and maintenance Interval days 7 14 28 365 56 Check stability of structure, tighten connections if required. Check parts at ground level for corrosion and/or rot. Replace any defective parts Check all painted elements for damage, rub down and repaint or replace as required. Check rotating pivot points for wear and smooth running lubricate or replace if required. Check rubber parts for wear and/or damage, replace if required. Check rubber safety surfaces for damage and poor performance, repair or replace if required. Check loose fill safety surfaces remove any foreign elements. repair or replace if required.

Disposal Instructions

All components should be broken down into categories of:-

- 1. Mild Steel - all swing frames, Playzone, Toddlerzone and Teenzone activities, deck frames and springle frames.
- Stainless Steel all slides, mirror panels. 2.
- **Aluminium** all Playzone and Toddlerzone posts. 3.
- Galavanised steel all chains and Teenzone posts. 4.
- Moulded rubber products without steel inserts all Toddlerzone and Playzone caps and panel edging.
- Timber all natural timber, plywood and mdf panels. 6.

Wherever possible these materials should be taken to a specialist recycling organisations and recycled. In some cases where composite materials are used then disposal at land fill sites is the only alternative such as:-

- Moulded rubber product with steel inserts all seats, deck tops, duo/dizzy disc tops. 7.
- High pressure laminate all Toddlerzone and Playzone panels. 8.
- Steel core polypropylene rope all scramble nets, space nets, Playzone and 9. Toddlerzone ropes and rope bridges.